

KET-PSC-100

Pulsante comando wireless in tecnologia X-Monitor



- Suitable for industrial environments
- High mechanical resistance
- LED indicator Programmable
- Battery powered

The button **KET-PSC-100** is suitable to be used as control element in industrial environments.

Used with the controllers of the X-Monitor can execute simple commands or complex (timed pressure, double-click, etc.) For the activation of different features.

The indicator LEDs incorporated can be controlled remotely and indicate the success of the operation.

The C-cell batteries provide a high level of autonomy while the degree of protection makes it suitable for even the harshest environments.

The command **KET-PSC-100** uses the network X-Monitor already.

It comes with membranes of different type to adapt to the most varied requirements.

TECHNICAL SPECIFICATIONS

Protection Range	IP65
Dimensions	80 x 82 x 57 mm (W x H x D)
Operative temperature	-15 +70 °C
Power supply	2 x C 1.5 V
RADIO MODULE	
Frequency	2.4 GHz
Antenna type	Internal
Output power	-10 +3 dBm
Sensitivity	-101 dBm
Compliance	IEEE 802.15.4 ZigBee Pro®
INTEGRATED CAPABILITIES	
Power meter	Integrated (LinkQuality)
Output power adjustment	From local keyboard and remotely
Firmware upgrade via radio	Yes

INFORMATION ORDERING

KET-PSC-100.N Neutral version
KET-PSC-100.L Version symbol light
KET-PSC-100.W Version symbol window
KET-PSC-100.D Version symbol door